

| UNIT HYDRO-PRO | TYPE | 5 | 7 | 10 | 13 |
|-------------------------------|-------------------|--------------|--------------|--------------|--------------|
| Part nr. | | 7018522 | 7018523 | 7018524 | 7018525 |
| Heating capacity A27/W27 | kW | 5 | 7 | 10 | 13 |
| Heating capacity A15/W25 | kW | 3.7 | 4.3 | 6.5 | 8.2 |
| Cooling capacity A35/W27 | kW | 2.8 | 3.5 | 5 | 7 |
| Power input | kW | 0.93 | 1.02 | 1.48 | 1.86 |
| Maximum swimming pool volume* | m ³ | 18 | 22 | 33 | 40 |
| Running current | A | 4.1 | 4.7 | 7 | 9.1 |
| Maximum current | A | 4.9 | 5.6 | 8.4 | 11 |
| Slow fuse current | A | 15 | 15 | 15 | 20 |
| COP at A27/W27 | | 5.8 | 5.9 | 6.2 | 6 |
| COP at A15/W25 | | 4 | 4.2 | 4.4 | 4.4 |
| Power supply | V/Ph/Hz | 220-240/1/50 | 220-240/1/50 | 220-240/1/50 | 220-240/1/50 |
| Controller | | Electronic | Electronic | Electronic | Electronic |
| Condenser | | Titanium | Titanium | Titanium | Titanium |
| Compressor type | | Rotary | Rotary | Rotary | Rotary |
| Refrigerant | | R410a | R410a | R410a | R410a |
| Air Flow | m ³ /h | 1600 | 2300 | 2300 | 2800 |
| Fan quantity | | 1 | 1 | 1 | 1 |
| Fan power input | W | 68 | 80 | 80 | 120 |
| Fan speed | RPM | 830/870 | 830/870 | 830/870 | 830/870 |
| Fan direction | | Horizontal | Horizontal | Horizontal | Horizontal |
| Noise level (10 m) | dB(A) | 39 | 40 | 40 | 43 |
| Noise level (1 m) | dB(A) | 48 | 49 | 49 | 52 |
| Water connection | mm | 50 | 50 | 50 | 50 |
| Nominal water flow | m ³ /h | 2.5 | 2.5 | 2.8 | 3.5 |
| Maximum pressure loss | kPa | 12 | 12 | 12 | 15 |
| Nett dimensions | L/W/H mm | 750/290/500 | 930/350/550 | 930/350/550 | 1000/360/620 |
| Shipping dimensions | L/W/H mm | 850/330/540 | 1060/380/590 | 1060/380/590 | 1120/380/660 |
| Net weight/shipping weight | Kg | 36/38 | 44/47 | 49/52 | 63/67 |

| UNIT HYDRO-PRO | TYPE | 18 | 22 | 22T | 26 | 26T |
|-------------------------------|-------------------|--------------|--------------|--------------|--------------|--------------|
| Part nr. | | 7018526 | 7018527 | 7018528 | 7018529 | 7018530 |
| Heating capacity A27/W27 | kW | 18 | 22 | 22 | 26 | 26 |
| Heating capacity A15/W25 | kW | 13 | 14.5 | 14.5 | 16.5 | 16.5 |
| Cooling capacity A35/W27 | kW | 10.8 | 11 | 11 | 15 | 15 |
| Power input | kW | 2.51 | 3.45 | 3.45 | 3.93 | 3.93 |
| Maximum swimming pool volume* | m ³ | 65 | 75 | 75 | 85 | 85 |
| Running current | A | 11.4 | 15 | 6.6 | 17.7 | 7.7 |
| Maximum current | A | 13.7 | 18 | 8.4 | 25 | 10 |
| Slow fuse current | A | 35 | 35 | 20 | 50 | 20 |
| COP at A27/W27 | | 6.1 | 5.9 | 5.9 | 5.8 | 5.8 |
| COP at A15/W25 | | 4.9 | 4.2 | 4.2 | 4.2 | 4.2 |
| Power supply | V/Ph/Hz | 220-240/1/50 | 220-240/1/50 | 380/3/50 | 220-240/1/50 | 380/3/50 |
| Controller | | Electronic | Electronic | Electronic | Electronic | Electronic |
| Condenser | | Titanium | Titanium | Titanium | Titanium | Titanium |
| Compressor type | | Scroll | Scroll | Scroll | Scroll | Scroll |
| Refrigerant | | R410a | R410a | R410a | R410a | R410a |
| Air Flow | m ³ /h | 3500 | 3500 | 3500 | 5600 | 5600 |
| Fan quantity | | 1 | 1 | 1 | 1 | 1 |
| Fan power input | W | 200 | 200 | 200 | 200 | 200 |
| Fan speed | RPM | 650 | 650 | 650 | 650 | 650 |
| Fan direction | | Vertical | Vertical | Vertical | Vertical | Vertical |
| Noise level (10 m) | dB(A) | 44 | 47 | 47 | 50 | 50 |
| Noise level (1 m) | dB(A) | 53 | 56 | 56 | 59 | 59 |
| Water connection | mm | 50 | 50 | 50 | 50 | 50 |
| Nominal water flow | m ³ /h | 4.6 | 6.2 | 6.2 | 7.1 | 7.1 |
| Maximum pressure loss | kPa | 16 | 18 | 18 | 18 | 18 |
| Nett dimensions | L/W/H mm | 865/685/910 | 865/685/910 | 865/685/910 | 865/685/910 | 865/685/910 |
| Shipping dimensions | L/W/H mm | 885/740/1050 | 885/740/1050 | 885/740/1050 | 885/740/1050 | 885/740/1050 |
| Net weight/shipping weight | Kg | 100/110 | 125/135 | 125/135 | 150/160 | 150/160 |

* Provided it is correctly insulated, calculation model: 5x heating capacity (A15/W25)