



Jet Swim 2000

An exclusive counter current unit with different settings. Pump capacity of 71 m³/h. The air flow that is mixed with the jet streams, is adjusted by turning the air knob on the front. It is just as simple to adjust the water flow.

Jet Swim 2000 is also available in 3-phase 230V/50Hz or 380V/60Hz. Contact Pahlén AB for information.

Technical data

Type	Motor	Voltage, 50Hz	Power, 230/400	Pump capacity	Pipe connection	Materials
2000	4.0 kW	230/400 V	13.9/8.0 A	71 m³/h	2 ½"	Bronze/stainless steel

Jet Swim 2000

Type of pool

Item no.	Type	Type of pool			
		Wood/plastic/ steel with liner	Concrete with liner	Concrete pool without liner	Fibreglass/PP-plastic
33029	Complete unit - concrete		x		
33028	Complete unit - liner	x			
1302000	Jet Swim unit	x	x	x	x
1302010	Assembly kit	x			x
1302020	Assembly kit		x	x	
1302015	Screw kit for fibreglass/PP pool				x
1302080	Pump 50Hz	x	x	x	x
1302080HZ	Pump 60Hz	x	x	x	x
1302090	Control box 400/3~	x	x	x	x

Soft

Start

Medium



Jet Massage in Classic model

The massage station can be controlled with a Pahlén circulation pump (e.g. FloVISE or P2000FLO) and Pahlén control box.

Jet Massage

Jet Massage consists of a standalone inlet, outlet and start button that combines as desired and up to 6 nozzles. All nozzles are made of acid-proof stainless steel AISI 316L and is available in both Marine and Classic designs.

Recommended flow capacity max 8-10 m³/h per nozzle.

Item no.	Type	steel/liner	concrete/liner	concrete/tiles	Pipe connection
130571	Start button Classic 350		x		
130570	Massage Soft Classic 350		x		Ø50 mm
130572	Massage Medium Classic 350		x		Ø50 mm
130561	Start button Classic	x		x (+12670)	
130560	Massage Soft Classic	x		x (+12670)	Ø50 mm
130562	Massage Medium Classic	x		x (+12670)	Ø50 mm
130551	Start button Marine 350		x		
130550	Massage Soft Marine 350		x		Ø50 mm
130552	Massage Medium Marine 350		x		Ø50 mm
130541	Start button Marine	x		x (+12670)	
130540	Massage Soft Marine	x		x (+12670)	Ø50 mm
130542	Massage Medium Marine	x		x (+12670)	Ø50 mm

For options to fibreglass/PP-plastic contact Pahlén AB for more information.