

Hi-Flow titanium 28-75kW

Hi-Flow titanium is a spiral heat exchanger made of titanium for the most demanding installations where there is a high risk of corrosion. Titanium is ideal for swimming pools with salt water or where a salt chlorinator is used. Adjustable stainless steel attachments included.

Maximum pressure secondary circuit (pool water) is 5 bar and primary circuit (hot water) is 30 bar.



Technical data		Capacity			Primary, hot water		Secondary, pool water	
Item no.	Type	kW	kBtu/h	kcal	l/min	press. drop H (m)	l/min	press. drop H (m)
11332	T28	28	95	24 075	20	1.0	300	1.1
11333	T40	40	135	34 393	40	2.3	350	1.7
11334	T75	75	260	64 488	45	5.2	350	1.7

Capacity at a temperature difference of 60°C for 11332 and 11333.

Capacity at a temperature difference of 70°C for 11334.

Hi-Flow 13-75kW

Hi-Flow is a spiral heat exchanger made of acid proof stainless steel AISI 316L for installations that operate under high pressure. Simple installation with the included adjustable stainless steel attachments.

Maximum pressure secondary circuit (pool water) is 8 bar and primary circuit (hot water) is 30 bar.



Technical data		Capacity			Primary, hot water		Secondary, pool water	
Item no.	Type	kW	kBtu/h	kcal	l/min	press. drop H (m)	l/min	press. drop H (m)
11391	HF13	13	45	11 177	25	0.9	200	0.6
11392	HF28	28	95	24 075	25	1.7	300	1.6
11393	HF40	40	135	34 393	60	1.3	300	1.6
11394	HF75	75	260	64 488	60	2.6	300	1.1

Capacity at a temperature difference of 60°C for 11391 and 11392.

Capacity at a temperature difference of 70°C for 11393 and 11394.